High pressure injection and paint spraying:

Airless A 4000 Airless A 5000

Aluminium or stainless steel









b&m Vertriebs-GmbH Material und Technik

Airless A 4000 / Airless A 5000

Technical features at a glance

Airless spray gun with ladder holder



Aircombi spray gun



Airless nozzles



HP injection sets



Injection packers



Wheel set A 4000

Field of application:

Airless A 4000 and A 5000 are electric Airless diaphragm pumps for the application of 1 and 2-component injection resins, liquid injection products, lacquers with a flame point over 21°C, water based paints, primers, filllers, wood protection products, wall paints, dispersion paints, fungizides, stains.

Description:

A 4000 and A 5000 are electric high pressure units with a working pressure from 0 up to 230 bar. Both models are available in aluminium or stainless steel version. Stainless steel version is recommended for use with alcalic and corrosive products.

Only electric power supply of 230 V is necessary for the operation, therefore A 4000 and A 5000 are suitable for building sites – no compressed air is needed. A 4000 is also available on a frame for mobile use in restauration and for easiest transport. Depending on the choice of accessories all models are suitable for the use as injection, airless and air assisted spray equipment.

The intake valve is completed with a trigger – in case of blocking the valve can be easy opened with the trigger. Working pressure is steplessly adjustable with the pressure regulator from 0 – 230 bar. Trolleys with big wheels enable easy transport also over stairs and on every building site. Integrated in the trolley is a tool box for storage of nozzles, injectors, filters etc.

Model A 5000 is also available with gas driven motor.

Technical Data	A 4000	A 5000	Choice of accessories:
Motor	0,75 KW	1,5 KW	– Hopper 6 ltr
Voltage / Frequency	230 V / 50 Hz	230 V / 50 Hz	– Hopper 30 ltr
Fuse	10 A Text	10 A	 Suction hose ass. lacquer
Power cord	3 mtr	3 mtr	Suction hose ass dispersion (A 5000)
Capacity / min	2,5 ltr	4,5 ltr	– HP-spray gun with swivel
Noise level	75 dB(A)	75 dB(A)	Choice of hp airless nozzlesHP injection gun
Max. working pressure	230 bar	230 bar	Injection gainInjection set with / without press.gauge
Hose length max.	20 mtr	40 mtr	- Nozzle extensions
Hose connection	M 16 x 1,5	M 16 x 1,5	– Brush cleaning set
Max. Nozzle size	0,021"	0,029"	 Digital flow meter
			– Wheel set A 4000

12/2008 Sucject of technical change without notice.

b&m agent in your area:

Permatech Concrete Solutions 18, Divya Darshan, Mount Mary Steps, Bandra (W), Mumbai- 400050. Tel: (022) 26441630 / (022) 26510146 www.permatech.in yogesh@permatech.in

Sales & Service: **b&m Vertriebs-GmbH** Ziegelmüllerstraße 6 D - 88094 Oberteuringen Tel. +49-(0)-7546-2626 Fax +49-(0)-7546-2630 www.bm-Vertriebs-GmbH.com info@bm-Vertriebs-GmbH.com