



2K – Injection Pump BMP 25015

Air operated 2-component injection equipment for pumping and injection of water proofing gels and resins.

With BMP 25015 acrylatic gels can be applicated with exact dosing ratio. Due to the compact design of the equipment BMP 25015 can be easily used on every building site. Either for water proofing injections in tunnels, cellars or on building sites were only small space is available.

Quick and easy cleaning can be made due to the separate flush pump which is integrated in the equipment.

The BMP 25015 has a fixed mixing ratio of 1:1. Continuous material flow, exact dosing, easy to operate technique are the features.

Technical Data:

Pressure ratio:	15:1
Capacity per double stroke	144 ccm
Max. operation pressure	120 bar
Order No. Basic equipment	HÜ81-0652174

Accessories:

Mixing valve cpl.	with HÜ81-0642617
cleaning device A + B	
Circulation set	HÜ81-0641970
Hopper assembly 6 ltr	HÜ81-0643529
Suction hose assembly	HÜ81-0641933
HP-hose dia 4 x 7,5 mtr	HÜ98-PPA1406 (3x)



b & m GmbH
Material und Technik

b & m GmbH
Zieglmüllerstr. 6
D - 88094 Oberteuringen
Phone 0049-7546-2626
Fax 0049-7546-2630

eMail: info@bm-gmbh.com
www.bm-GmbH.com