
Crack injectors, accessories ...

Plastic injectors for wood and walls



Injector D 6,5 / D 9,5 with / Without nippel for wood



Fixing tool with and

Without head piece




With nipple



Crack injectors steel made or aluminium with head valve



Standard crack injector steel or aluminium available in sizes from D 10/70 to D 20/200



Special lengths up to 500 mm





in almost every length required.

For further products please refer to our price list.



Free flow injectors Bajonett fitting



Slide coupling

Iniectors w.

nipple D 12 / 14 / 16 / 18

Integrated ball valve

For quick injections without waiting time: Quick site injectors with bottom valves



Alu-Kompact Injector

Modular system for low

pressure injection:

Ball tap, lamella injector, connecting piece

4-jaw-coupling for

cone head nipples

With integrated bottom valve. Multi usable pressure piece. Diameter 14 mm. Lengths from 85 mm up to 300 mm. With cone head or Flat head nipple.

Quick site injector with nominal break point



Quick site injector 13/110

With nominal break point. With non return valve No pre-mounting Non-return-valve and Nipple pre-mounted.

Fixing tool for accu drills optional available.

.







With ball tap





Injection set rigid with

Hp injection gun

Quick lock fitting for Lamella plastic injectors



Hammer drills with SDS Plus / SDS Max fitting



Filling tubes with ball tap

Gauge and ball tap



Hand lever guns


Order form for b & m injection guide: How to do professional injections.

	How to do hig Explanations the right crac Brochure with Price / each (
	We order her
Company	Company:
b & m Vertriebs-GmbH Ziegelmüllerstr. 6	Street:
D – 88094 Oberteuringen	Post Code/To
	Name of pers
	Tel. / Fax:

Please send us a cheque with the value of ordered brochures Along with the order form and we will supply free destination.

... Enjoy your job with b & m!









Injection guns Paint spray guns



Working safety and working tools: Googles, gloves, overalls: Please ask for our price list.

Brush set for nozzle cleaning

high quality injections? The injection guide will help you. is how to choose the suitable equipment, how to find ack injectors, how to do step-by-step injections. ith 20 pages and coloured pictures, easy to understand. $n \in 8.50$ including mail charges.

ereby Stk. b & m injection guide à € 8.50

Town:

erson in charge:



Technical Solutions for Renovation and Water Proofing





Injection and Material Filling

Supplier:

b & m Vertriebs-GmbH Ziegelmüllerstr. 6 D – 88094 Oberteuringen Tel. 0049 – 7546 – 2626 Fax 0049 - 7546 - 2630 E-mail: bm-Vertriebs-GmbH@t-online.de

Sales and service in your area:

Permatech Concrete Solutions 18, Divya Darshan, Mount Mary Steps, Bandra (W), Mumbai - 400050. Tel : (022)26510146 Fax : (022) 26441630 Email :yogesh@permatech.in

Filling, transporting and injecting of water based, mineral and cementary based products:

Screw Pump BMP 6 Professional allround unit

- Cementary grouts
- Suspensions
- Mortars up to 2,5 mm
- Plasters
- Fire protection mortars Silicate products
- Filled epoxies
- Micro cement



Filling and injecting at low costs

Screw Pump BMP 5

- Silicates
- Water glass
- Micro cement
- Fungicides
- Micro emulsion

Available with 6 and 30 ltr hopper. A wide range of accessories enables you to cover almost any application in the field of injecting and spraying pigmented grouts.

Lime wash

Suspensions

Wood protection

Pigmented paints

Application of 2 component Acrylat Gel

Professional technic in stainless steel: BMP 14025 2K 1:1

Pneumatic piston pump with 2 material pumps and separate flush pump in stainless steel. Available with hoppers or suction hoses. The components are transefered separately to the static mixing valve. Due to the new designed mixing valve a separate cleaning of the material valves is possible. Mixing ratio fixed at 1 : 1

How to choose the suitable equipment for your material? Please refer to our selection chart on page 3!

Transfer and injection of resins and water based products **Coating – Impregnating – Spraying**

Electric diaphragm-Airless-units: Mobile as no compressed air is needed.

Airless A 4000 Small, versatile, mobile

Airless A 5000 Strong but inexpensive





Also available with wheel-set

Field of application:

• Inside dispersion paints • Micro emulsions • Impregnations • Silicates and stone protection **Only A 10000:** Roof and facade painting, fire protection paints, anti corrosion paints All models available in stainless steel – especially recommended for alcalic products.

> Pneumatic Airless piston pumps Inox: Suitable for explosion proof areas!





BMP 433 VP

BMP 6552

EP-resins, PUR-resins (1-/2-K), silicates, fungicides, pest control, lacquers, varnish, micro emulsion, water based paints Air motor is driven by compressed air. Compressor needed. Pneumatic units available up to 416 bar pressure.

> How to inject like a professional? Our injection guide will help you. Please refer to order sheet page 6

All units on this page are available with hopper or suction hoses. With suitable accessories all units are usable for spray application as well.



Also with remote control cable!

Voltage 230 V for every building site

Highly recommended for spray application of bituminous and

cementary water proofing.

Detachable into 3 parts. Patented.

Airless A 10000 suitable for 2 guns



• Epoxy resins • PUR-resins (1-/2-K) • Silikate • Injection cremes • Fungicides • Lacquers • Stains





For small quantities, highest pressure:

Drill injection pump "Jumper"

Jumper 230 V Motor is an electric drilling machine For epoxy and PUR-resins

Equipment Materials	Hand Lever Gun	A 4000 / 5000 Electric	A 10000 Electric	BMP 433-1 Pneumatic	BMP 6 Electric	BMP 14025 Pneumatic	Jumper Electric	BMP 5 Electric
Material transport	Piston manual	Diaphragm Electric	Diaphragm Electric	Piston Air driven	Screw pump Electric	Piston Air driven	Hand drill Electric	Screw pump Electric
Pressure range	0 – 400 bar	0 – 230 bar	0 – 230 bar	0 – 264 bar	0 – 20 bar	200 bar	0 – 400 bar	0 – 25 bar
Voltage		230 Volt	230 Volt	1	230 Volt	1	230 Volt	230 Volt
Mixing ratio	Pre-mixed.	Pre-mixed	Pre-mixed	Pre-mixed	Pre-mixed	1:1	Pre-mixed	Pre-mixed
Material feed	310 ml or 1000 ml	6 Itr hopper/ Suction tube	6 Itr hopper/ Suction tube	6 Itr hopper Suction tube	30 ltr Hopper	Suction tube / Hopper set	Hopper 2 Itr	Hopper 6 I Hopper 30 Itr
Capacity max/ltr		2,5 /4,5 ltr / min	6,5 ltr / min	3,0 ltr / min	12 ltr/min	8 ltr / min	1 ltr / min	12 ltr / min
Compressor needed	N	No	No	Yes	For spraying only	Yes	No	For spraying only
Air Supply Itr/min				200 ltr / min	200 – 500 ltr			150 ltr
Suitable for EX-areas	Yes	No	No	Yes	No	Yes	No	No
Weight	1 kg	25 kg / 54 kg	60 kg	20 kg	25 kg	40 kg	6 kg	15 kg
Materials								
1-K-PUR-Resin	0	0	0	0	×	×	0	×
2-K-PUR-Resin	0	0	0	0	×	×	0	×
2-K-Epoxy Resin	0	0	0	0	×	×	0	0
Micro cement	×	Partly	Partly	×	0	×	×	0
Suspensions	×	×	×	×	0	×	×	0
Bore hole grouts	×	×	×	×	0	×	×	0
Filling mortars*	×	×	×	×	*0	×	×	*0
Silicate fluids	×	0	0	0	Partly	×	×	0
Injection creme	×	0	0	0	Partly	×	×	0
Lime wash	×	×	×	×	0	×	×	0
Acrylic-Gel	×	×	×	×	×	0	×	×
PUR-Gel	×	×	×	×	×	×	×	×
Fungicides	×	0	0	0	Partly	×	×	0
Wood protection	×	0	0	0	×	Х	×	0
Varnish/lacquers	×	0	0	0	×	×	×	0
Dispersion paints	×	Partly	0	×	0	×	×	0
Spray plasters	×	×	×	×	0	×	×	0
Liquid wall paper	×	×	×	×	0	×	×	0
Bituminous sealings.	×	×	×	×	0	Х	×	Partly
Sealing grouts	×	×	×	×	0	Х	×	0
Releasing agents	×	0	0	0	×	×	×	0
Legend:	O = Very suitable		X = Not suitable		*Depending on grain size	rain size		
	2							